

MATERIAL SAFETY DATA SHEET

Section 1. Product and Company Identification

Product Name:	5 Second Quickie Polish Dryer	DATE:	4/20/2007
Formula:	30-3098	REV.	NEW
Item#:	12525		

Manufacturer: American International Industries
 2220 Gaspar Ave
 Los Angeles, CA 90040

Chem-Tel: (800) 255-3924

Section 2. Composition / Information on Ingredients

Hazardous Ingredients:

Component	CAS #	%	Exposure Limits ppm	
			ACGIH-TWA	OSHA-PEL
Hexamethyldisiloxane	107-46-0	95-100	None Established	None Established

Section 3. Hazardous Identification

Potential Health Effects, Signs and Symptoms of Exposure:

Primary Route of Entry: Eyes, skin or inhalation

Eye: May cause slight eye irritation.

Skin: May cause slight skin irritation. Causes drying of skin.

Ingestion: Low-harmful

Inhalation: Low-harmful


Section 4. First Aid Measures

First Aid for Eye: Immediately flush with water for 15 minutes, including under eyelids. Seek medical attention if discomfort persists.

First Aid for Skin: Wash off affected areas with plenty of soap and water. If discomfort or irritation persists contact a physician.

First Aid for Inhalation: Remove to fresh air. Seek medical attention if discomfort persists.

First Aid for Ingestion: Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person. Seek prompt medical attention.



MATERIAL SAFETY DATA SHEET

Section 5. Fire Fighting Measures

Flash Point (°F/°C): -1°C (30.2°F) Closed Cup

Flammable Limit (vol%): LEL: 1.00%
UEL: 38.0%

Auto-ignition Temp. (vol%): None Established

Extinguisher Media: Foam, dry chemical or carbon dioxide.

Fire Fighting Procedures: Use supplied breathing air and protective clothing. Highly flammable.

Unusual Fire and Explosion Hazards: Vapors form explosive mixtures with air.
Vapors may travel considerable distance to source of ignition and flash back.

Section 6. Accidental Release Measures

Spill or Release Procedures: Shut off all ignition sources. Contain the spill or leak. Scrape up with rag and place in a container.


Section 7. Handling and Storage

Handling & Storing: Keep container closed when not in use. Store in cool place. Keep away from heat, sparks and flame. Do not lay the container on its side. Use with proper ventilation. Avoid prolonged breathing vapor. Avoid contact with eyes and prolonged or repeated skin contact. Static electricity may accumulate and cause a fire hazard.
Information about the empty container: Do not re-use the container. Container will be very hazardous when emptied. Residues will be explosive or flammable. Keep away from heat, sparks and flame. Do not puncture or cut the container and do not weld on or near the container.

Section 8. Exposure Controls / Personal Protective Equipment

Exposure Guidelines: ACGIH TLV-TWA: Not established
OSHA PEL: Not established

Respiratory Protection (specify type): Not required.



MATERIAL SAFETY DATA SHEET

Ventilation: Local Exhaust: Recommended.
 Mechanical (general): Adequate ventilation system.
 Special: Unknown.
 Other: Unknown.

Protective Gloves: Plastic film or rubber gloves.

Eye Protection: Safety glasses.

Other Protective equipment: Eyewash equipment.

Work/Hygienic Practices: Keep away from heat, sparks and flame. Avoid prolonged breathing vapor. Avoid contact with eyes and prolonged or repeated contact with skin. Wash hands and gargle after handling.

Section 9. Physical and Chemical Properties

Appearance @ 25°C: Transparent colorless fluid	Viscosity (RVT): Not applicable
Odor @ 25°C: Odorless	Vapor Pressure: 35mmHg (25°C)
pH: Not applicable	Vapor Density: 5.6 (air=1)
Specific Gravity: 0.760 (25°C)	Evaporation Rate: > 1.0 (Butyl Acetate =1)
Ignition: Not applicable	
Melting Point: -68°C	
Boiling Point: 100°C	
Solubility in Water: Insoluble	

Section 10. Stability and Reactivity

Stability: Stable

Hazardous Decomposition Products:

Thermal breakdown of this product during fire or very high heat condition may evolve the following hazardous decomposition product: Carbon oxides and traces of incompletely burned carbon compounds. Silicon dioxide.


Incompatibility (Materials to Avoid):

None

Hazardous Polymerization:

Will not occur

Conditions to Avoid: Flame, Electric spark, static and heat.



MATERIAL SAFETY DATA SHEET

Section 11. Toxicological Information

Skin Irritation: Skin-Rabbit: 500mg/24hr MILD

Eye Irritation: Ocular Instillation-Rabbit: Almost negative (as an eye irritant)

Sensitization: No significant effects were observed. (Guinea Pig)

Acute Toxicity (LC50): LC50 (oral/Rat): >5g/kg

Acute Toxicity (LC50): No adverse effect (Inhalation/Guinea pig): 25,000ppm/30min.

Subacute Toxicity: Dose of high concentration may develop increased organ weight in small animals.

Chronic Toxicity: No information is available.

Carcinogenicity: NTP: not listed, OSHA REGULATED: Not listed

Mutagenicity: No evidence of mutagenicity.

Section 12. Ecological Information

Biodegradation: No evidence of biodegradation.

Bioaccumulation: May cause bioaccumulation.

Aquatic Toxicology: NOEL (Fathead minnow): 200-900ppb


Other Information: Vapor undergoes indirectly photolysis in the troposphere.

Section 13. Disposable Considerations

Can be burned in chemical incinerator equipped with afterburner and scrubber but exert extra care in igniting as the product is very flammable. Do not dispose of the emptied container unless the contents have been completely removed and container has been flushed with a clean neutral solvent and then dried up. Do not dispose the emptied container unlawfully. Observe all federal, state, and local laws.

Section 14. Transportation Information

<IMO Information>



MATERIAL SAFETY DATA SHEET

ID No.: UN 1993
Classification and Class: Flammable Liquids / Class 3.2
Packaging Group: II
Proper Shipping Name: Flammable Liquids, N.O.S.
Technical Shipping Name: Organosiloxane
Marine Pollutant: None

<DOT Information>

ID No. (49CFR 172.101): UN 1993
Hazard Class (49CFR 172.101): 3, Flammable Liquid
Packaging Group (49CFR 172.101): II
Proper Shipping Name (49CFR 172.101): Flammable Liquids, N.O.S.
Technical Shipping Name: Organosiloxane

Section 15. Regulatory Information

Toxic Substance Control Act (TSCA) Status: Listed on the TSCA Inventory.

European Inventory of Existing Commercial Chemical Substances (EINECS) Status: Listed on the EINECS.

Labeling According to EC-Regulations Required:

Symbol: F
R-Phrase: (R-11) Highly Flammable
S-Phrase: (S-7/9) Keep container tightly closed and in a well-ventilated place.
(S-16) Keep away from sources of ignition - No smoking
(S-51) Use only in well-ventilated areas.

Contains: Methylsiloxane 100%

Superfund Amendments and Reauthorization Act of 1996 (SARA) Title III Section 313 Supplier Notification:

This regulation requires submission of annual reports of toxic chemical(s) that appear in section 313 of the emergency planning and community Right-To-Know Act of 1986 and 40 CFR 372. This information must be included in all MSDS's that are copied and distributed for the material. The toxic chemical(s) contained in this product are: None.

California Proposition 35:

This regulation requires a warning for California Proposition 65 Chemical (s) under stature. The California Proposition 65 Chemical (s) contained in this product are: None

Section 16. Other Information

No additional information available.