

MATERIAL SAFETY DATA SHEET

Section 4. First Aid Measures

First Aid for Eye: Immediately flush with water for 15 minutes, including under eyelids. Seek medical attention if discomfort persists.

First Aid for Skin: Wash off affected areas with plenty of soap and water. If discomfort or irritation persists contact a physician.

First Aid for Inhalation: Remove to fresh air. Seek medical attention if discomfort persists.

First Aid for Ingestion: Rinse mouth out with water. Only induce vomiting if directed by a physician. Never give anything by mouth to an unconscious person. Seek prompt medical attention.

Section 5. Fire Fighting Measures

Flash Point (°F/°C): 24°F (-4.44°C)TCC

Flammable Limit (vol%): LEL: 1.7%
UEL: 12.0%

Auto-ignition Temp. (vol%): None Established

Extinguisher Media: Foam, dry chemical or carbon dioxide.

Fire Fighting Procedures: Full protective equipment, including self contained breathing apparatus is recommended. Water from fog nozzle may be used to cool containers to prevent pressure build up.


Unusual Fire and Explosion Hazards: When heated above the flash point flammable vapors may be emitted. Fine mists or sprays may be flammable at temperatures below the flash point.

Section 6. Accidental Release Measures

Spill or Release Procedures: Highway or railway spills call chemtrec (800) 424-9600 cont. U.S. Collect (202) 483-7616 from Alaska and Hawaii.

Stay upwind and away from spill. Keep all sources of ignition and hot metal surfaces away from spill. Keep out of drains, sewers, or waterways. Use sand or other inert material to dam and contain spill. Do not flush with water; use absorbent pads. For large spills call response team and notify appropriate state/local agencies. Immediately notify the National Response Center (phone number: 800-424-880; in case if the spill is in excess of EPA reportable quantity.

Section 7. Handling and Storage



MATERIAL SAFETY DATA SHEET

Handling & Storing: In accordance with good industrial practice avoid unnecessary personal contact. Wash face and hands before eating, drinking, or smoking. Store in original container, away from excessive heat and keep in a dry are.

Section 8. Exposure Controls / Personal Protective Equipment

For Manufacturing Use Only:

Ventilation: Use local Exhaust.

Protective Gloves: Neoprene gloves.

Eye Protection: Include splash guards and side shields.

Respiratory Protection: Use with adequate Ventilation and avoid breathing vapors.

Clothing: Coveralls.

Other Protective Eye bath and shower.

Section 9. Physical and Chemical Properties

Appearance @ 25°C: Colored viscous liquid	Viscosity (RAT): Not applicable
Odor @ 25°C: Sweet Ester Odor	Vapor Pressure: Not Available
pH: Not applicable	Vapor Density: Not Available
Specific Gravity: 7.746lb/gl	Evaporation Rate: Slower than ether
Ignition: Not applicable	Coating V.O.C.: 1.44 lb/gl
Melting Point: Not applicable	Material V.O.C.: 1.44 lb/gl
Boiling Range: 171°F - 640°F	
Solubility in Water: Moderate	


Section 10. Stability and Reactivity

Stability: Stable

Hazardous Decomposition Products:
CO, CO2, Nitrous Oxides, Smoke

Incompatibility (Materials to Avoid):
Acids, Alkalies and Peroxides.

Hazardous Polymerization:



MATERIAL SAFETY DATA SHEET

Will not occur

Conditions to Avoid: Do not store over 120°F

Section 11. Toxicological Information

Results of component toxicity test performed:

No data

Human experience:

No data

Section 12. Ecological Information

Ecological Information:

No data

Chemical Fate Information:

No data

Section 13. Disposable Considerations

RCRA 40 CFR 261 Classification:

Federal, State and local laws governing disposal of materials can differ. Ensure proper disposal compliance with proper authorities before disposal. Do not incinerate in closed containers

Section 14. Transportation Information

<DOT Information>

Proper Shipping Name:	Paint
DOT Hazard Class:	3, Flammable Liquid
Packaging Group:	II
UN ID Number	UN 1263

Section 15. Regulatory Information

Regulatory Information Available Upon Request

Section 16. Other Information

Reference numbers are as follows:

MATERIAL SAFETY DATA SHEET

Item Number	Formula	Shade Description
45501	30-1400	Santa Fe
45502	30-0989	Smoke House
45503	30-0476	Notorious
45504	30-1123	Tar Pit
45505	30-7029	Platinum Dust
45507	30-8361	Cotton Cloud
45509	30-8370	Hamptons
45510	30-0458	Tea Party
45511	30-0484	Frosted Cake
45512	30-0460	Light Hearted
45514	30-0434	Velvet Box
45515	30-0453	Brick House
45517	30-0492	Hot Pepper
45518	30-1445	Beachball
45519	30-7717	Santorini
45521	30-0478	Emperor's Clothes